

## DEEP UNDERCOUNTER REFRIGERATORS

| Model           | Doors/<br>Drawers | Cu.<br>Ft. | # of<br>Shelves | HP  | Amps | Crated<br>Weight | Cabinet Dimensions              |                                  |                                  |
|-----------------|-------------------|------------|-----------------|-----|------|------------------|---------------------------------|----------------------------------|----------------------------------|
|                 |                   |            |                 |     |      |                  | L                               | D†                               | H*                               |
| TUC-44          | 1/0               | 11.4       | 2               | 1/5 | 5.1  | 285              | 44 <sup>1</sup> / <sub>2</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-60-32       | 2/0               | 15.9       | 4               | 1/5 | 5.1  | 355              | 60 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-67          | 2/0               | 20.6       | 4               | 1/5 | 5.1  | 375              | 67 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-93          | 3/0               | 30.9       | 6               | 1/2 | 9.7  | 520              | 93 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-119         | 4/0               | 43.9       | 8               | 1/2 | 12.0 | 660              | 119 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| <b>DRAWERED</b> |                   |            |                 |     |      |                  |                                 |                                  |                                  |
| TUC-44D-2       | 0/2               | 11.4       | N/A             | 1/5 | 5.1  | 285              | 44 <sup>1</sup> / <sub>2</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-60-32D-2    | 1/2               | 15.9       | 2               | 1/5 | 5.1  | 365              | 60 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-67D-2       | 1/2               | 20.6       | 2               | 1/5 | 5.1  | 415              | 67 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-67D-4       | 0/4               | 20.6       | N/A             | 1/5 | 5.1  | 460              | 67 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-93D-2       | 2/2               | 30.9       | 4               | 1/2 | 9.7  | 575              | 93 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-93D-4       | 1/4               | 30.9       | 2               | 1/2 | 9.7  | 610              | 93 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-93D-6       | 0/6               | 30.9       | N/A             | 1/2 | 9.7  | 655              | 93 <sup>1</sup> / <sub>4</sub>  | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-119D-2      | 3/2               | 43.9       | 6               | 1/2 | 12.0 | N/A              | 119 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-119D-4      | 2/4               | 43.9       | 4               | 1/2 | 12.0 | N/A              | 119 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-119D-6      | 1/6               | 43.9       | 2               | 1/2 | 12.0 | N/A              | 119 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-119D-8      | 0/8               | 43.9       | N/A             | 1/2 | 12.0 | N/A              | 119 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |

† Depth does not include 1" for rear bumpers or 1/4" for front bumper.

\* Height does not include 6<sup>1</sup>/<sub>4</sub>" for castors or 6" for optional legs.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.

## DEEP UNDERCOUNTER FREEZERS

| Model      | Doors/<br>Drawers | Cu.<br>Ft. | # of<br>Shelves | HP  | Amps | Crated<br>Weight | Cabinet Dimensions             |                                  |                                  |
|------------|-------------------|------------|-----------------|-----|------|------------------|--------------------------------|----------------------------------|----------------------------------|
|            |                   |            |                 |     |      |                  | L                              | D†                               | H*                               |
| TUC-44F    | 1/0               | 11.4       | 2               | 1/2 | 10.2 | 300              | 44 <sup>1</sup> / <sub>2</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-60-32F | 2/0               | 15.9       | 4               | 1/2 | 10.4 | 385              | 60 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-67F    | 2/0               | 20.6       | 4               | 3/4 | 11.7 | 400              | 67 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |
| TUC-93F    | 3/0               | 30.9       | 6               | 3/4 | 10.2 | 530              | 93 <sup>1</sup> / <sub>4</sub> | x 32 <sup>1</sup> / <sub>4</sub> | x 29 <sup>3</sup> / <sub>4</sub> |

† Depth does not include 1" for rear bumpers or 1/4" for front bumper.

\* Height does not include 6<sup>1</sup>/<sub>4</sub>" for castors or 6" for optional legs.



TUC-44



TUC-60-32D-2



TUC-93

Deep Undercounter models hold full-sized pans. (2 per drawer)

| DEEP TUC MODELS      |
|----------------------|
| Heavy, 16 Gauge Tops |
| All TUC-44 models    |
| All TUC-60-32 models |
| All TUC-67 models    |
| All TUC-93 models    |

| Heavy Duty Package:                                                                |
|------------------------------------------------------------------------------------|
| 20 gauge door, 20 gauge sides,<br>20 gauge back, 16 gauge top & stainless interior |
| TUC-44HD / TUC-44F-HD                                                              |
| TUC-60-32HD / TUC-60-32F-HD                                                        |
| TUC-67HD / TUC-67F-HD                                                              |
| TUC-93HD / TUC-93F-HD                                                              |

## FEATURES/BENEFITS

- Oversized, environmentally friendly refrigeration system (refrigerators: 134A / freezers: R404A).
- Refrigerator holds 33°F to 38°F temperature; freezer holds -10°F.
- Automatic defrost system on freezer models time-initiated, time-terminated.
- 360° circular airflow for uniform product cooling.
- All stainless steel front, top and sides.
- Interior - attractive, NSF approved, white aluminum sides and top, coved corners and 300 series stainless steel floor.
- Aluminum finished back.
- Features the combined advantage of convenient undercounter placement with deeper refrigerated storage.
- Easily slides under counters, maximizes space for refrigerated food storage in fast food line-up.
- Recessed handles.
- Doors swing within cabinet dimensions.
- Work surface 36" high.
- Adjustable, heavy duty, PVC coated wire shelves (not available in drawered sections).
- Foamed-in-place high density polyurethane insulation (CFC free).
- 5" diameter castors standard equipment (legs available).
- Front breathing.
- Self-contained system.
- Heavy, 16 gauge tops available (excludes -119 models) upcharge applies.
- Door models accommodate half bun tray rack; applies to only one door of TUC-60-32 (18" x 26" sheet pan) - not included.
- Available with optional 3" diameter castors.
- **Drawered Models**
- Accommodates two 12"L x 20"W x 8"D full size pans or four 1/2 pans or six 1/3 pans per drawer. Pans not included.
- Door/drawer combination models require customer to designate door/drawer orientation.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.